

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0706 12" x 60" Short Bed Jointer with Spiral Cutterhead



MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 3 HP, 220V, single-phase motor
- Spiral cutterhead with sixty 4-sided indexable carbide inserts
- Quiet and efficient serpentine belt drive power transfer
- Easy-to-reach pedestal mounted controls
- Handwheel-controlled parallelogram-style tables
- Precision-ground cast-iron table only measures 60" long, yet offers 12" wide cutting space

The Model G0706 is available for \$2,195. As with all Grizzly products, the Model G0706 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

MODEL G0706

12" X 60" SHORT BED JOINTER W/ SPIRAL CUTTERHEAD

Product Dimensions:

Weight 695 lbs.
 Length/Width/Height 60" x 30³/₄" x 43¹/₄"
 Foot Print (Length/Width)..... 39³/₈" x 22³/₈"

Shipping Dimensions:

Type Wood
 Content..... Machine
 Weight..... 834 lbs.
 Length/Width/Height..... 63" x 34" x 39"

Electrical:

Power Requirement 220V, Single-Phase, 60 Hz
 Switch..... Magnetic with Thermal Overload Protection
 Switch Voltage 220V
 Cord Length 13 feet
 Cord Gauge 12 gauge
 Minimum Circuit Size 20A
 Plug Included No
 Recommended Plug Type NEMA 6-20

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower 3 HP
 Voltage 220V
 Phase Single
 Amps 15A
 Speed 3450 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer..... Serpentine Belt Drive
 Bearings Shielded and Permanently Sealed

Main Specifications:

Cutting Capacities

Bevel Jointing 45°, 90°, 135°
 Maximum Width of Cut..... 12"
 Maximum Depth of Cut For a Single Pass..... 1/8"
 Maximum Rabbeting Depth..... 3/8"
 Number of Cuts Per Minute..... 19,800

Fence Information

Fence Length	31¼"
Fence Width	1⅞"
Fence Height	5⅞"
Fence Stops	45°, 90°, 135°

Cutterhead Information

Cutterhead Type.....	Spiral
Cutterhead Diameter	3¾"
Number of Cutter Spirals.....	4
Number of Indexable Cutters	60
Cutter Insert Type.....	Carbide
Cutter Insert Length.....	14mm
Cutter Insert Width	14mm
Cutter Insert Thickness	2mm
Cutterhead Speed	4950 RPM

Table Information

Table Length	60"
Table Width	13"
Table Thickness	4⅞"
Floor to Table Height.....	31½"

Construction

Body Assembly Construction	Cast Iron
Cabinet Assembly Construction	Steel
Fence Assembly Construction.....	Cast Iron
Guard Construction	Aluminum
Table Construction	Cast Iron
Parallelogram	Yes
Paint	Powder Coated

Table Information

Table Adjustment Type	Handwheel
Table Movement Type.....	Parallelogram

Other Information

Number of Dust Ports.....	1
Dust Port Size	5"

Other Specifications:

Customer Setup and Cleaning Time.....	30 Minutes
Warranty.....	1 Year
ISO Factory.....	ISO 9001
Country of Origin.....	China
Serial Number Location	ID Label on Center of the Stand

Features:

- Parallelogram Table Adjustment
- Fence is Center Mounted with Positive Stops at 45°, 90°, and 135°
- Heavy-Duty Steel Cabinet
- Independently Adjustable, Handwheel Precision Table Movement
- Serpentine Drive Belt
- Stress Relieved Infeed and Outfeed Tables
- Pedestal Mounted ON/OFF Switch
- Cast Aluminum Guard
- 5" Dust Port